

ALINCO

Quality. Style. Performance!

VHF FM Handheld Transceiver

DJ-VX11

UHF FM Handheld Transceiver

DJ-VX36/VX41



Ready for your toughest challenge!

Alinco introduces a line of handheld FM transceivers that is IP-67 compatible water/dust proof. Ready to take on your need for high-quality communications, these tough performers do much more than just the "basics", they're loaded with essential features such as VOX, Voice Encryptions / Compander, Scan / Skip, Various Alarm features and more!



■ High Power Output

The standard Li-Ion battery allows VX11 to produce up to 5 watts, VX36/VX41 to 4 watts with Mid 2W and Low 0.5W settings.

■ Plenty of programmable channels

128 channels are available in 8 groups, up to 16ch each.

Advanced Features

- 128 channels to program operating parameters via PC utility dealer software (Optional cable required for programming)
- Comes with a rechargeable 1800mAh Li-Ion pack, desktop quick-charger, belt clip and high-performance whip antenna (May vary depending on dealers' sales policy)
- IP67 compatible water/dust proof, ergonomically designed compact body
- CTCSS/DCS/DTMF signaling features programmable
- External microphone and speaker ports
- Internal VOX, Voice-prompt in English, Remote-Kill/Stun/Revive, Analog scrambling, Voice compander, Repeater-reverse, Busy-Channel-Lockout, Time-Out-Timer and more



Standard accessories

Specifications

GENERAL

Frequency Coverage	[DJ-VX11] 136-174MHz [DJ-VX36] 340-400MHz [DJ-VX41] 400-470MHz
Modulation	F3E(16K0F3E / 11K0F3E)
Frequency stability	±2.5ppm
Power supply requirement	7.4V (Battery)
Current drain (Approx.)	1500mA TX / 300mA receive at Max audio output 80mA squelched
Usable temperature range	-20~+60°C(-4~140°F)
Channel step	2.5, 6.25 KHz
Dimensions	118 x 59 x 38 mm (with battery pack)
Weight	approx.230g inclusive of battery pack and antenna

TRANSMITTER

Output Power (Approx)	Approx. 5W(VHF) / 4W(UHF) / 2W / 0.5W
Frequency Deviation	±5kHz / ±2.5kHz
Spurious emission	Less than -27dBm

RECEIVER

Receiver System	Direct conversion
Sensitivity (12dB SINAD)	-12dBu
Adjacent Channel Selectivity	Wide More than 60dB / Narrow More than 60dB
Audio output power	1W (10% distortion)

Specifications subject to change without notice or obligation.
Product intended for use by properly authorized operators.

Standard Accessories (A strap is included)

Whip antenna	Li-Ion Battery Pack	Rapid Charger Stand	AC Adapter	Belt Clip
VX11 : EA-254 VX36 : EA-258 VX41 : EA-259	EBP-101 Li-Ion 7.4V 1800mAh	EDC-219	EDC-220	EBC-51

Standard accessories declared herein are our factory default and may vary at moment of sales depending on the market and Dealers' sales policy.

Options



● Earphone Microphone (EME-56A)



● Speaker Microphone (EMS-76)

Authorized Dealer:

Copyright Alinco, Inc., Osaka, Japan. All rights reserved. Although Alinco has designed this brochure to be as accurate and comprehensive as possible, we reserve the right to make changes at any time to our equipment line, optional accessories, specifications, standard accessories, or availability of any such devices we manufacture and distribute. Please note that certain products and accessories may not be available in all countries of distribution therefore consult your Authorized Alinco Dealer for product availability and pricing. Colors of images herein may appear slightly different from actual products due to print.
* Projections are not included in the declared dimension values.
* Operator license may be required. Please consult your dealer for details.

ALINCO, INC. Electronics Division

Yodoyabashi Dai-Bldg 13F, 4-4-9 Koraibashi,
Chuo-ku, Osaka 541-0043 Japan
Phone: +81-6-7636-2362 Fax: +86-6-6208-3801
http://www.ALINCO.com
E-mail: export@alinco.co.jp

FNFNELNE-PE
Ver.1.0 DJVX11
Printed in Japan