

Ultra compact and simple to operate fixed mount VHF marine radio

- Output power selectable 25W/1W
- IPX7 Watertight
- Dual-watch & Tri-watch
- DSC functions supported
- Weather Alert
- Large, bright display with alphanumeric name tags
- Position Indication on display (Optional GPS receiver required)



Specifications

GENERAL

Frequency range	Tx : 156.025-157.425MHz Rx : 156.050-163.275MHz
Frequency stability	±10ppm
Emission type	FM (16K0G3E), DSC(16K0G2B)
Antenna impedance	50 Ω
Rated voltage	13.8V ±15%
Current Consumption	1.5A (Max audio output) 5.5A (TX 25W)/ 1.5A (TX 1W)
Operating temperature	-20~+60°C
Ingress protection	IPX7
Dimensions (WxHxD)	153mm × 67mm × 152mm approx.
Weight (approx.)	742g (with microphone)

TRANSMITTER

RF Output Power	25W/1W
Modulation Type	Variable Reactance
Spurious Emission	≥70dB
Frequency deviation	± 5KHz

RECEIVER

Circuit	Double-Conversion Superheterodyne
Intermediate Frequencies	1st: 21.7 MHz 2nd: 450 kHz
Sensitivity	0.22μV (12 dB SINAD)
Adjacent Channel Selectivity	70 dB
Intermodulation response	70 dB
Audio Output (External speaker)	4.5W (4Ω10 %THD)

* Specifications and contents on this brochure subject to change without notice or obligation.

Standard accessories

- DC cable (ADUA98)
- Mounting bracket & Fixing hardware
- Microphone hanger

Authorized Dealer:

Copyright Alinco, Inc., Osaka, Japan. All rights reserved. Although Alinco has designed this brochure to be as accurate and comprehensive as possible, we reserve the right to make changes at any time to our equipment line, optional accessories, specifications, standard accessories, or availability of any such devices we manufacture and distribute. Colors of images herein may appear slightly different from actual products due to print. Declared dimension values are approximate and projections are not included. Please consult with your dealer about license requirement before purchase.

ALINCO, INC. Electronics Division

Yodoyabashi Dai-Bldg 13F, 4-4-9 Koraibashi,

Chuo-ku, Osaka 541-0043 Japan

Phone: 06-7636-2362 Fax: 06-6208-3802

<http://www.ALINCO.com>

E-mail: export@alinco.co.jp



FNFNLE-PE
Ver.1.0 MX1MX15
Printed in Japan